




Position the fasteners where you want them.



A connectivity to suit your needs

Power supply adaptable
power supply 12 or 24 VDC

uvoji
beyond UV LED

Triggering in running order or by flow meter

Choice of operation indicator:
visual or remote



THE UV LED
DISINFECTON
SOLUTION
FOR INSTANT
HEALTHY WATER

OJI MICRO



THE PERFECT ALLY
TO INTEGRATE INTO
YOUR EXISTING
SYSTEMS



Fogging, nebulisation



Food & beverage

uvoji
Cap Alpha,
9 avenue de l'Europe,
34 830 Clapiers
France

www.uvoji.com
commercial@uvoji.fr

N° de siret : 82152143200020
Ne pas jeter sur la voie publique



THE ADVANTAGES OF OJI MICRO

1

A product of small size for an installation to all your systems

2

A modular and customisable product for answer easily for all your needs

3

A product without consumables and maintenance-free.
*Up to 5,000 hours

4

99.999% irradiation efficiency for viruses and bacteria

5

Robust for optimum installation

OJI MICRO



TECHNICAL SPECIFICATIONS

	MICRO 1		MICRO 2			
Max flow rate gpm	0.53	0.79	0.53	0.79	1.05	1.32
UV dose (mj/cm ²)	>33	>23	>48	>33	>26	>20
* > à 98 % UV T						
Alimentation	12V - 24V		12V - 24V			
Overall (in)	L2.75 x L1.93 x H1.93		L2.75 x L1.93 x H1.93			
Weight (Lbs)	0.036		0.036			
Puissance électrique	12 W		18W			
Air temperature	32 - 131°F		32 - 131°F			
Water temperature	32 - 113°F		32 - 113°F			
Pressure (PSI)	72.50		72.50			

APPLICATIONS



Food
&
beverage



Fogging
&
nebulisation



ACCESSORIES

Hydraulic connector	Quick Connect 3/8
Triggering	Order of operation
Back to information	Operating status, product fault

OPTIONS

