

UNIK 5000

Pressure Sensing Platform

The new UNIK 5000 is a high performance configurable solution to pressure measurement. The use of micromachined silicon technology and analogue circuitry enables best in class performance for stability, low power and frequency response. The new platform enables you to easily build up your own sensor to match your own precise needs. This high performance, configurable solution to pressure measurement employs modular design and lean manufacturing techniques.

High Quality

The combination of a high technology sensor, together with advanced signal conditioning and packaging techniques, provides an ideal long term solution for reliable, accurate and economical measurements.

Bespoke as Standard

Custom-built from standard components, manufacturing sensors to your requirement is fast and simple; each UNIK 5000 is a “bespoke” pressure sensing solution, but with the short lead times and competitive pricing you would expect from standard products.

Expertise

We have the people and the knowledge to support your needs for accurate and reliable product performance; our team of experts can help you make the right sensor selection, guiding you and providing the help and tools you need. It is important to ensure that the sensor material and performance selected are suitable for your application.



Features

- Ranges from 70 mbar (1 psi) to 700 bar (10000 psi)
- Accuracy to $\pm 0.04\%$ Full Scale (FS) Best Straight Line (BSL)
- Stainless Steel construction
- Frequency response to 3.5 kHz
- High over pressure capability
- Hazardous Area certifications
- mV, mA, voltage and configurable voltage outputs
- Multiple electrical and pressure connector options
- Operating temperature ranges from -55 to $+125^{\circ}\text{C}$ (-67 to $+257^{\circ}\text{F}$)
- Online configuration tool

UNIK 5000 Specifications

Measurement

Operating Pressure Ranges:

Gauge Ranges

Any zero based range 70 mbar to 70 bar
(1 to 1000 psi)

Note: All psi values are approximate.

Sealed Gauge Ranges

Any zero based range 10 to 700 bar
(145 to 10000 psi)

Absolute Ranges

Any zero based range 100 mbar to 700 bar
(1.5 to 10000 psi)

Differential Ranges

Wet/Dry

Uni-directional or bi-directional 70 mbar to 35 bar
(1 to 500 psi)

Wet/Wet

Uni-directional or bi-directional 350 mbar to 35 bar
(5 to 500 psi)

Line pressure: 70 bar (1000 psi) maximum

Barometric Ranges

Barometric ranges are available with a minimum span of 350 mbar (5.1 psi)

Non-Zero Based Ranges

Non-zero based ranges are available. For non-zero based gauge ranges, please contact Druck to discuss your requirements.

Over Pressure

- 10 × FS for ranges up to 150 mbar (2 psi)
- 6 × FS for ranges up to 700 mbar (10 psi)
- 2 × FS for barometric ranges
- 4 × FS for all other ranges (up to 200 bar for ranges ≤70 bar and up to 1200 bar for ranges >70 bar)*

For differential versions the negative side must not exceed the positive side by more than:

- 6 × FS for ranges up to 150 mbar (2 psi)
- 4 × FS for ranges up to 700 mbar (10 psi)
- 2 × FS for all other ranges up to a maximum of 15 bar (200 psi)

Containment Pressure

- Ranges up to 150 mbar (2 psi) gauge 10 × FS
Ranges up to 70 bar (1000 psi) gauge 6 × FS
(200 bar (2900 psi) max)
- Ranges up to 70 bar (1000 psi) absolute
200 bar (2900 psi)
- Ranges above 70 bar (1000 psi)
- 1200 bar (17400 psi)*

Differential (-ve port) must not exceed positive port by more than 6 × FS (15 bar (200 psi) maximum.

* 600 bar (8700 psi) for pressure connector options
PX, RA and RF

Supply and Outputs

Electronics Option	Description	Supply voltage (V)	Output	Current Consumption (mA)
0	mV Passive	2.5 to 12	10 mV/V [^]	<2 at 10 V
1	mV Linearised	7 to 12	10 mV/V [^]	<3
2	mA	7 to 28**	4-20 mA	<30
3	0 to 5 V 4-wire	7 to 16**	0 to 5 V	<3
4	0 to 5 V 3-wire	7 to 16**	0 to 5 V*	<3
5	Basic Configurable (3-wire)	See below	See below	<3
6	0 to 10 V 4-wire	12 to 16**	0 to 10 V	<3
7	0.5 V to 4.5 V Ratiometric	5.0 ± 0.5	0.5 to 4.5 V	<3
8	Configurable (4-wire)	7 to 36	See below	See below
9	Configurable (3-wire)	7 to 36	See below	See below

[^] with a 10 V supply mV output sensors give 100 mV over the full scale pressure.

- Output is ratiometric to the supply voltage
- Output reduces pro-rata for pressure ranges below 350 mbar (5 psi)

*0 to 5 V 3-wire output is non true zero. At pressures below 1% of span the output will be fixed at approximately 50 mV

**32 V in non-hazardous area operation

~ Supply voltage is between [Maximum Output + 1 V] (7 V minimum) to 16 V (32 V in non-hazardous area operation)

Basic Configurable (Option 5), Configurable 4-Wire (Option 8), Configurable 3-Wire (Option 9)

Any pressure signal output configurations will be available, subject to the following limitations:

Output Specification	Basic Configurable (Option 5)	Configurable (Options 8, 9)
Minimum span:	4 V	2 V
Maximum span:	10 V	20 V
Maximum output limit:	11 V	±10 V
Maximum zero offset:	Span / 2	±Span
Current consumption:	< 3 mA	< 20 mA @ 7 Vdc decreasing to < 5 mA @ 32 Vdc
Reverse output response:	No	Yes
Maximum operating temperature:	+125°C	+80°C

Output voltage range can be specified to a resolution of 0.1 V.

The output will continue to respond to 110% FS. i.e. if a 0 to 10 V output is specified, the output will continue to increase proportionally to applied pressure until at least 11 V.

Option 5: Not true zero, the output will saturate at < 50 mV.

Options 8, 9: On startup <100 mA drawn for 10 ms typically.

Options 8, 9: Shunt calibration: not available with reverse output.

Examples

Configuration	Allowed	Not Allowed
Basic Configurable (Option 5)	0 to 5 V	1 to 4 V (span too small)
	0.5 to 4.5 V	4 to 11 V (offset too big)
	1 to 6 V	
	1 to 11 V	
Configurable (Options 8, 9)	-10 to 0 V	0 to 12 V (outside ± 10 V limits)
	0 to 5 V	6 to 10 V (offset too big)
	-5 to 5 V	0 to 0.5 V (span too small)
	-2 to 10 V	
	1 to 6 V	
	10 to 0 V	

Power-Up Time

- mV, Voltage and current versions: 10 ms
- Configurable 3-wire and 4-wire versions: 500 ms

Insulation

- 500 Vdc: 100 M Ω
- 500 Vac: ≤ 5 mA leakage current (mV and mA versions only)

Shunt Calibration

Shunt Calibration provides a customer accessible connection which, when applied, causes a shift in output of 80% FS in order to simulate applied pressure. It is fitted to the mV, Configurable 4-wire and Configurable 3-wire versions as standard. It is not available with DIN, M12 x 1 or M20 x 1.5 electrical connectors (options 7, D, G and R).

Shunt calibration is activated in different ways depending on the electrical connector and version:

- mV versions: connect Shunt Cal to -ve Supply or where available, connect both Shunt Cal connections together.
- Configurable 4-wire and Configurable 3-wire versions: connect Shunt Cal to -ve Output or, where available, connect both Shunt Cal connections together.

Note: Not available with reverse output.

Performance Specifications

There are three grades of performance specification: Industrial, Improved and Premium.

Accuracy

Voltage, Current and mV Linearised

Combined effects of non-linearity, hysteresis and repeatability:

- Industrial: $\pm 0.2\%$ FS BSL
- Improved: $\pm 0.1\%$ FS BSL
- Premium: $\pm 0.04\%$ FS BSL

mV Passive

≤ 70 bar

Industrial/Improved: $\pm 0.25\%$ FS BSL

Premium not available

> 70 bar

Industrial/Improved: $\pm 0.5\%$ FS BSL

Premium not available

Note 1: For the barometric pressure range, accuracy is of span, not full scale.

Note 2: For bi-directional ranges, accuracy is specified for each direction separately.

Zero Offset and Span Setting

Demountable electrical connector options allow access to potentiometers that give at least $\pm 5\%$ FS adjustment (see Electrical Connector section).

Factory Set To:

Product Description	Industrial	Improved and Premium
Current and Voltage Versions (Demountable Electrical Connections and Cable Gland)	$\pm 0.5\%$ FS	$\pm 0.2\%$ FS
Current and Voltage Versions (All Other Electrical Connections)	$\pm 1.0\%$ FS	$\pm 1.0\%$ FS
mV Versions	± 3.0 mV	± 3.0 mV

Long Term Stability

$\pm 0.05\%$ FS typical ($\pm 0.1\%$ FS maximum) per year increasing pro-rata for pressure ranges below 350 mbar

Temperature Effects

Four compensated temperature ranges can be chosen. Industrial Accuracy performance:

- 10 to +50°C (+14 to +122°F): $\pm 0.75\%$ FS TEB*
- 20 to +80°C (-4 to +176°F): $\pm 1.5\%$ FS TEB
- 40 to +80°C (-40 to +176°F): $\pm 2.25\%$ FS TEB
- 40 to +125°C (-40 to +257°F): $\pm 2.25\%$ FS TEB

*TEB = Temperature Error Band

Improved and Premium Accuracy performance:

- 10 to +50°C (+14 to +122°F): $\pm 0.5\%$ FS TEB
- 20 to +80°C (-4 to +176°F): $\pm 1.0\%$ FS TEB
- 40 to +80°C (-40 to +176°F): $\pm 1.5\%$ FS TEB
- 40 to +125°C (-40 to +257°F): $\pm 1.5\%$ FS TEB

Temperature effects increase pro-rata for pressure ranges below 350 mbar (5 psi) and are doubled for barometric ranges.

Line Pressure Effects (Differential Version Only)

Zero shift: $< \pm 0.03\%$ span/bar of line pressure

Span shift: $< \pm 0.03\%$ span/bar of line pressure

Effects increase pro-rata for differential pressure ranges below 700 mbar (10 psi).

Physical Specifications

Environmental Protection

- See Electrical Connector section
- Hyperbaric Pressure: 20 bar (300 psi) maximum

Operating Temperature Range

See Electrical Connector section

Pressure Media

Fluids compatible with stainless steel 316L and Hastelloy C276.

For the wet/dry differential version, negative pressure port: Fluids compatible with stainless steel 316L, stainless steel 304, Pyrex, silicon and structural adhesive.

Enclosure Materials

Stainless steel (body), nitrile- or silicone-rubber (o-rings, gaskets), EPDM (gaskets), PVDF (depth cone), PTFE (vent filter), Nickel plated brass (lock rings), glass filled nylon (electrical connector assemblies), delrin (depth cone). Cable sheaths as specified (see Electrical Connector).

Pressure Connector

Available options are:

- G1/4 Female*
- G1/4 Male Flat
- G1/4 Male 60° Internal Cone
- G1/4 Male Flat Long
- G1/4 Male Flat with Snubber
- G1/4 Male Flat with Cross Bore Protection
- G1/4 Male with Nipple
- G1/4 Quick Connect
- G1/8 Male 60° Internal Cone
- G1/2 Male via Adaptor*
- 1/4 NPT Female*
- 1/4 NPT Male
- 1/8 NPT Male
- 1/8-27 NPT Female
- 1/2 NPT Male via Adaptor
- 7/16-20 UNJF Female*
- 7/16-20 UNF Male Short Flat*
- 7/16 UNF Long 37° Flare Tip*
- 7/16-20 UNJF Male 74° External Cone
- 3/8-24 UNJF
- 1/4 Swagelok Bulkhead
- M10 X 1 80° Internal Cone
- M12 X 1 60° Internal Cone
- M14 X 1.5 60° Internal Cone
- M20 X 1.5 Male (3 mm bore)
- M20 X 1.5 Male (8 mm bore)
- Depth Cone (G1/4 Female Open Face)
- M12 x 1.0 74° External Cone
- Quick Release Male
- VCR Female*
- VCR Male*
- NW16 Flange
- R3/8 Male
- R1/4 Male

Choose connectors marked * for pressure ranges over 70 bar. Other pressure connectors may be available, contact Druck to discuss your requirement.

General Certifications

CRN Certified 0F13650.517890YTN ADD1/REV1, 0F13828.2 (sensor types K and O) and CSA 0F13650.56 ADD1 for pressure ranges up to and including 350 bar (5000 psi).

Electrical Connector

Various electrical connector options are available offering different features:

Code No.	Description	Maximum Operating Temperature Range		IP Rating	Zero/ Span Adjust
		°C	°F		
0	No Connector	-55 to +125	-67 to +257	-	Y
1	Cable Gland	-40 to +80	-40 to +176	65	N
2	Raychem Cable	-55 to +125	-67 to +257	65	N
3	Polyurethane Depth	-40 to +80	-40 to +176	68	N
4	Hytrel Depth	-40 to +80	-40 to +176	68	N
6/E	Bayonet MIL-C-26482	-55 to +125	-67 to +257	67	N
7	DIN 43650 Form A Demountable	-40 to +80	-40 to +176	65	Y
A/F	Bayonet MIL-C-26482 Demountable	-55 to +125	-67 to +257	65	Y
C	1/2 NPT Conduit	-40 to +80	-40 to +176	65	N
D	Micro DIN (9.4 mm pitch)	-40 to +80	-40 to +176	65	N
G	M12x1 4pin	-55 to +125	-67 to +257	67	N
K	Zero Halogen Cable Demountable	-40 to +80	-40 to +176	65	Y
N	Kynar Depth	-40 to +80	-40 to +176	68	N
R	M20 x 1.5 Inline	-40 to +80	-40 to +176	65	Y

Note 1: Electronics output options 8 and 9 are restricted to a maximum operating temperature of 80°C (176°F).

Note 2: Hazardous area approved versions are restricted to a maximum operating temperature range of -40°C to +80°C (-40°F to +176°F).

Note 3: Electrical connector option R IP65 rating only with suitable conduit/cable fitting.

CE Conformity

- RoHS 2011/65/EU
- Pressure Equipment Directive 2014/68/EU Sound Engineering Practice
- ATEX 2014/34/EU (Optional)
- EMC Directive 2014/30/EU
- BS EN 61000-6-1: 2007: Susceptibility - Light Industrial
- BS EN 61000-6-2: 2005: Susceptibility - Heavy Industrial*
- BS EN 61000-6-3: 2007+A1:2011: Emissions - Light Industrial
- BS EN 61000-6-4: 2007+A1:2011: Emissions - Heavy Industrial
- BS EN 61326-1: 2013: Electrical Equipment for Measurement, Control and Laboratory Use
- BS EN 61326-2-3: 2013: Particular Requirements for Pressure Transducers

*PMP/PTX models with electrical connector options 6, A, C, E, F, G, N and R with cable screen connected to case.

Hazardous Area Approvals (optional)

General applications:

- IECEx/ATEX Intrinsically Safe 'ia' Group IIC
- INMETRO Intrinsically Safe 'ia' Group IIC
- NEPSI Intrinsically Safe 'ia' Group IIC
- FM Approved (Canada & US) Intrinsically Safe Exia Class I, Division 1, Groups A, B, C & D and Class I, Zone 0 AEx/Ex ia Group IIC; Single Seal

Mining applications:

- IECEx/ATEX Intrinsically Safe 'ia' Group I
- INMETRO Intrinsically Safe 'ia' Group I

For full certification details, refer to the type-examination certificates (or approval listings) and supplied hazardous area installation instructions.

Electrical Connector

Connector Type	Option code	Electronics Option						
			4 to 20 mA	Voltage (3-wire) and Basic Configurable	Voltage (4-wire)	Configurable Voltage (4-Wire)	Configurable Voltage (3-Wire)	mV
Molex	0	1 Red	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply
		2 Yellow	-	+ve Output	+ve Output	+ve Output	+ve Output	+ve Output
		3 Green	-	-	-ve Output	-ve Output	0V Common	-ve Output
		4 Blue	-ve Supply	0V Common	-ve Supply	-ve Supply	0V Common	-ve Supply
		5 Orange	-	-	-	Shunt Cal	Shunt Cal	Shunt Cal
		6 Black	Case	Case	Case	Case	Case	-
Cable (Not Raychem)	1, 3, 4, C, N	Red	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply
		Yellow	-	+ve Output	+ve Output	+ve Output	+ve Output	+ve Output
		Blue	-	-	-ve Output	-ve Output	0V Common	-ve Output
		White	-ve Supply	0V Common	-ve Supply	-ve Supply	0V Common	-ve Supply
		Orange	-	-	-	Shunt Cal	Shunt Cal	Shunt Cal
		Black	-	-	-	-	-	-
Raychem Cable	2	Screen	-	-	-	-	-	-
		Red	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply
		White	-	+ve Output	+ve Output	+ve Output	+ve Output	+ve Output
		Green	-	-	-ve Output	-ve Output	0V Common	-ve Output
		Blue	-ve Supply	0V Common	-ve Supply	-ve Supply	0V Common	-ve Supply
		Black	-	-	-	Shunt Cal	Shunt Cal	Shunt Cal
Bayonet	6, A	Screen	-	-	-	-	-	-
		A	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply
		B	-ve Supply	+ve Output	+ve Output	+ve Output	+ve Output	+ve Output
		C	-	-	-ve Output	-ve Output	0V Common	-ve Output
		D	-	0V Common	-ve Supply	-ve Supply	0V Common	-ve Supply
		E	-	-	-	Shunt Cal	Shunt Cal	Shunt Cal
DIN A Micro DIN	7 D	F	-	-	-	-	-	Shunt Cal
		1	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply
		2	-ve Supply	0V Common	-ve Supply	-ve Supply	0V Common	-ve Supply
		3	-	+ve Output	+ve Output	+ve Output	+ve Output	+ve Output
		E	Case	Case	-ve Output	-ve Output	0V Common	-ve Output
		F	-	-	-	Shunt Cal	Shunt Cal	-
Bayonet Alternative Wiring Options	E, F	A	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply
		B	-	0V Common	-ve Supply	-ve Supply	0V Common	-ve Supply
		C	-	+ve Output	+ve Output	+ve Output	+ve Output	+ve Output
		D	-ve Supply	-	-ve Output	-ve Output	0V Common	-ve Output
		E	-	-	-	Shunt Cal	Shunt Cal	Shunt Cal
		F	-	-	-	Shunt Cal	Shunt Cal	-
M12 X 1 4-Pin	G	1	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply
		2		+ve Output	+ve Output	+ve Output	+ve Output	+ve Output
		3	-ve Supply	0V Common	-ve Supply	-ve Supply	0V Common	-ve Supply
		4	Case	Case	-ve Output	-ve Output	0V Common	-ve Output
Zero Halogen Cable (Demountable)	K	Pink	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply	+ve Supply
		White	-	+ve Output	+ve Output	+ve Output	+ve Output	+ve Output
		Green	-	-	-ve Output	-ve Output	0V Common	-ve Output
		Blue	-ve Supply	0V Common	-ve Supply	-ve Supply	0V Common	-ve Supply
		Grey	-	-	-	Shunt Cal	Shunt Cal	Shunt Cal
		Brown	-	-	-	-	-	-
		Yellow	-	-	-	-	-	-
		Screen	-	-	-	-	-	-
M20 x 1.5 Female Demountable	R	+ve	+ve Supply	-	-	-	-	-
		-ve	-ve Supply	-	-	-	-	-

Ordering Information *(see the online configuration tool at Druck.com)*

(1) Select model number

Main Product Variant															
PMP	Amplified Pressure Transducer														
PDCR	mV Pressure Transducer														
PTX	4-20 mA Pressure Transmitter														
	Product Series														
	5	UNIK 5000													
	Diameter and Material														
	0	25mm Stainless Steel													
	Electrical Connector (Note 6)														
	0	No Electrical Connector (Note 7)													
	1	Cable Gland (Polyurethane Cable)													
	2	Raychem Cable													
	3	Polyurethane Cable (Depth)													
	4	Hytrel Cable (Depth)													
	6	MIL-C-26482 (6-pin Shell Size 10) (Mating connector not supplied)													
	7	DIN 43650 Form A Demountable (Mating connector supplied)													
	A	Demountable MIL-C-26482 (6-pin Shell Size 10) (Mating connector not supplied)													
	C	1/2" NPT Conduit (Polyurethane cable)													
	D	Micro DIN (9.4 mm Pitch) (Mating connector supplied)													
	E	MIL-C-26482 (6 pin Shell Size 10) Alternative Wiring (Mating connector not supplied)													
	F	Demountable MIL-C-26482 (6 pin Shell Size 10) Alternative Wiring (Mating connector not supplied)													
	G	M12 x 1 4-pin male (Mating connector not supplied)													
	K	Zero Halogen Cable Demountable													
	N	Kynar Cable (Depth)													
	R	M20 x 1.5 Inline Female Conduit Demountable (Note 8)													
	Electronics Option														
	0	mV Passive 4-wire (PDCR) (Note 1)													
	1	mV Linearised 4-wire (PDCR)													
	2	4 to 20 mA 2-wire (PTX)													
	3	0 to 5 V 4-wire (PMP)													
	4	0 to 5 V 3-wire (PMP)													
	5	Basic Configurable 3-wire (PMP)													
	6	0 to 10 V 4-wire (PMP)													
	7	0.5 to 4.5 V Ratiometric 3-wire (PMP) (Note 5)													
	8	Configurable 4-wire (PMP) (Note 4, 5)													
	9	Configurable 3-wire (PMP) (Note 4, 5)													
	Compensated Temperature Range														
	TA	-10 to +50 °C (-14 to +122 °F)													
	TB	-20 to +80 °C (-4 to +176 °F)													
	TC	-40 to +80 °C (-40 to +176 °F)													
	TD	-40 to +125 °C (-40 to +257 °F) (Note 2, 5)													
	Accuracy														
	A1	Industrial													
	A2	Improved													
	A3	Premium													
	Calibration														
	CA	Zero/Span Data													
	CB	Room Temperature													
	CC	Full Thermal													
	CR	Room Temperature/Measured Reading													
	Hazardous Area Approval (Note 6)														
	H0	None													
	H1	IECEx/ATEX Intrinsically Safe 'ia' Group IIC													
	H2	IECEx/ATEX Intrinsically Safe 'ia' Group I													
	H6	FM (C & US) Intrinsically Safe 'ia' Group IIC/ABCD													
	HA	IECEx/ATEX Intrinsically Safe 'ia' Groups I/IIC [H1 + H2]													
	HS	IECEx/ATEX/FM (C & US) Intrinsically Safe 'ia' Groups IIC/ABCD [H1 + H6]													
	J1	IECEx/ATEX/NEPSI Intrinsically Safe 'ia' Group IIC													
	JA	INMETRO Intrinsically Safe 'ia' Group IIC													
	JB	INMETRO Intrinsically Safe 'ia' Group I													
	JF	INMETRO Intrinsically Safe 'ia' Group I/IIC [JA + JB]													
	Pressure Connector														
	PA	G1/4 Female (Note 3)													
	PB	G1/4 Male Flat													
	PC	G1/4 Male 60° Internal Cone													
	PD	G1/8 Male 60° Internal Cone													
	PE	1/4 NPT Female (Note 3)													
	PF	1/4 NPT Male													
	PG	1/8 NPT Male													
	PH	M20x1.5 Male (3 mm bore)													
	PJ	M14x1.5 60° Internal Cone													
	PK	M12x1 Internal Cone													
	PL	7/16-20 UNJF Male 74° External Cone													
	PN	G1/2 Male via Adaptor (Note 3)													
	PQ	G1/4 Quick Connect													
	PR	1/2 NPT Male via Adaptor (Note 3)													
	PS	1/4 Swagelok Bulkhead													
	PT	G1/4 Male Flat Long													
	PU	7/16-20 UNF Long 37° Flare Tip (Note 3)													
	PV	7/16-20 UNJF Female (Note 3)													
	PW	Depth Cone (G1/4 Female Open Face)													
	PX	7/16-20 UNF Male Short Flat (Note 3, 9)													
	PY	3/8-24 UNJF													
	PZ	M10 x 1 80° Internal Cone													
	RA	VCR Female (Note 3, 9)													
	RB	G1/4 Male Flat with Snubber													
	RC	G1/4 Male Flat with Cross Bore Protection													
	RD	M12 x 1.0 74° External Cone													
	RE	Quick Release Mount													
	RF	VCR Male (Note 3, 9)													
	RJ	M20 x 1.5 Male (8 mm bore)													
	RQ	NW16 Flange													
	RT	1/8-27 NPT Female													
	RU	R3/8 Male													
	RV	R1/4 Male													
	RW	G1/4 Male with Nipple													
PTX	5	0	7	2	-	TA	-	A2	-	CB	-	H0	-	PA	(Example Model Number)

Ordering Notes

Note 1: Premium Accuracy is not available on this version

Note 2: Please ensure that the electrical connector selected is option 0, 2, 6, A, E, F or G.

Note 3: Select one of these pressure connectors for pressure ranges over 70 bar

Note 4: Maximum operating temperature is 80°C (176°F)

Note 5: Hazardous area certifications not available

Note 6: Hazardous area certifications are restricted by electrical connector options in line with the following table:

Connector														
Approval	0	1	2	3	4	6/E	7	A/F	C	D	G	K	N	R
H0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
H1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	-	-	Y
H2	Y	-	Y	Y	Y	Y	-	-	Y	-	Y	-	-	-
H6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	-	-	Y
HA	Y	-	Y	Y	Y	Y	-	-	Y	-	Y	-	-	-
HS	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	-	-	Y
J1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	-	-	Y
JA	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	-	-	Y
JB	Y	-	Y	Y	Y	Y	-	-	Y	-	Y	-	-	-
JF	Y	-	Y	Y	Y	Y	-	-	Y	-	Y	-	-	-

Note 7: Available with component certification, use of which requires incorporation into certified apparatus with an IP rated enclosure appropriate to the certification type supplied

Note 8: Electronics option 2 only

Note 9: Pressure ranges less than 500 bar

2) State pressure range and units (e.g., 0 to 10 bar, -5 to +5 bar)

Pressure unit options are:

Symbol	Description
bar	bar
mbar	millibar
psi	pounds/sq. inch
Pa	Pascal
hPa	hectoPascal
kPa	kiloPascal
MPa	MegaPascal
mmH ₂ O	mm water
cmH ₂ O	cm water
mH ₂ O	metres water
inH ₂ O	inches water
ftH ₂ O	feet water
mmHg	mm mercury
inHg	inches mercury
kgf/cm ²	kg force/sq. cm
atm	atmosphere
Torr	torr

3) State pressure reference (e.g., gauge)

Reference options are:

- gauge
- absolute
- barometric
- sealed gauge
- wet/dry differential
- wet/wet differential

4) State cable lengths and units

Integer values only, e.g. 1 m cable, 8 ft. Minimum length 1 m (3 ft) cable (only required with certain electrical connectors).

Maximum cable length 100 m (300 ft) for approval options not H0; 200 m (600 ft) for approval option H0.

5) Output options 5, 8 and 9

State voltage output at minimum and maximum pressure (e.g., output -1 to 9 V)

Typical order examples

PTX5012-TB-A2-CA-H0-PA: 0 to 10 bar, gauge, 3 m cable

PMP5028-TC-A3-CC-H0-PE: -15 to 75 psi, gauge, 15 ft cable, output voltage -1 to 5 volts

PDCR5071-TB-A1-CB-H0-PA: 0 to 100 bar, sealed gauge

Accessories (order as separate line items)

P/N 202-034-05: Sensor termination enclosure

P/N 600-914: Desiccant gel pack for STE

P/N 222-117-01: Short sink weight (to fit G1/4 female)

P/N 222-179-01: Depth cone injection moulded for PW connection

P/N 163-009: Mating connector for MIL-C-26482

(Electrical connector options 6, A, E, and F) (**Note 10**)

Cable Assemblies (Note 10)

A made up electrical connector with a length of cable.

(1) Select Part Number

Main Product (Note 10)

UNIKCABLE

Cable assembly

Electrical connector

6

MIL-C-26482

7

DIN 43650

D

MICRO DIN (9.4 mm Pitch)

Cable

1

Polyurethane cable (Note 11)

2

Raychem cable

UNIKCABLE - 6 - 2 (Example Part Number)

(2) State cable length and units (Integer value only)

Minimum length 1 m (3 ft)


Maximum length 200 m (600 ft)

Example: UNIKCABLE-6-2 5 m

Note 10: Not considered suitable for use in hazardous areas.

Note 11: This cable is the same as that used in the electrical connector cable gland (Option 1 in the main product).

Mechanical Drawings



Druck.com

Copyright 2019. Baker Hughes Company. This material contains one or more registered trademarks of Baker Hughes Company and its subsidiaries in one or more countries. All third-party product and company names are trademarks of their respective holders.

920-483L

Baker Hughes